



- * El Ranger 66 es una solución muy económica con características suficientes para operar la mayoría de aplicaciones POS.
- * Fabricación Industrial que le permitirá operar con mucha tranquilidad.
- * Además permite la conexión de otros periféricos.

- * Procesador INTEL J1900 QUAD CORE 2.42GHz
- * Diseño 100% Fanless.
- * Diseño ultra delgado.
- * Pantalla Bezel – Free de 15”
- * Diseño de componentes y circuitos industriales.
- * Accesorios disponibles opcionales: Lector de banda magnética y display para el cliente.





System	
CPU Support	Intel® Celeron® Processor Bay-Trail J1900 up to 2.42Ghz
Memory	Support up to 2GB DDR3
Core Logic	Intel® Bay-Trail
Net Work	10/100/1000 Base-T Fast Ethernet
Power Supply	12V Power Adaptor
System weight	5.8 Kgs
Dimension	384 x 324 x 194 (WxHxD) mm
O/S	Windows7, POSReady 7, Windows 8, Windows 10
Storage	
SSD	SSD SATA
I/O Ports	
Serial Ports	3 x external COM
USB Ports	4 x external USB Ports
mPCIe	-
Ethernet	1 x 10/100/1000 Mbps (RJ45)
PS/2	-
VGA	1 x DB-15 VGA Interface
Parallel Port	-
Audio	-
Cash Drawer	1 x RJ11 (12V)
DC-IN	12V DC-IN
Power Switch	1 x Power Switch
Display	
LCD	15" TFT LCD Panel
Max. Resolution	1024 x 768
Brightness	250 nits
Touch Screen	5 wire resistive touch panel (Flat Touch Screen)
Environmental	
Operating Condition	0°C ~ 40°C, 20%RH ~ 90%RH
Storage Condition	-20°C ~ 60°C, 10%RH ~ 90%RH
Peripheral Options	
Customer Display	VFD Type, 20 columns x 2 lines, each column 5x7 dotsRS232 (Default) , Multi-language / Epson Commands
MSR	JIS-I or II, ISO Track 1 / 2 / 3 USB (default)
Safety standards	CE/FCC

