



- Lector IMAGE 2D.
- Alto performance de tecnología de imagen.
- Lectura de códigos desde celular o pantalla de computador.
- Reconstruye códigos de barras dañados.
- Norma de seguridad IP-52.



Operating Mode	Hand-held, Auto-detection
Programming Method	Manual (reading special barcode)
Firmware Upgrade	Online
Input Voltage	5 ± 0.25 VDC
Power	Standby: 0.40 W, Working: 1.20 W
Current	Standby: 80 mA, Working: 240 mA
Image Size	640 × 480 pixels
Imager Field of View	Horizontal: 40°, Vertical: 30°
Scanning Angle	±60°, ±40°, 360° (skew, pitch, roll)
Print Contrast	20% minimum reflective difference
Decoding Capability	1D: UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (Bookland EAN), ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5 (Discrete 2 of 5), Matrix 2 of 5, Codabar (NW7), Code 128, UCC/EAN 128, ISBT 128, Code 93, Code 11 (USD-8), MSI/Plessey, UK/Plessey, China Post, China Finance, Telepen, GS1 DataBar (formerly RSS) variants
	2D: PDF417, QR Code, DataMatrix, Han Xin Code, Aztec Code, MicroQR Code
Minimum Resolution	5 mil, 1 mil = 0.0254 mm
Decoding Depth	5 mil Code39 (3 chars): 1.5 cm – 5.5 cm
	13 mil UPC (6 chars): 0.5 cm – 13.0 cm
	20 mil Code39 (5 chars): 4.0 cm – 18.0 cm
	6.7 mil PDF417 (20 chars): 1.0 cm – 8.2 cm
	10 mil DM (20 chars): 1.0 cm – 8.0 cm
	20 mil QR (20 chars): 1.5 cm – 16.5 cm

